

Advantages

- Easy to Use
- Rugged Field Use Design
- Temperature Compensated
- 1-3 Year Recommended Calibration Intervals
- Record and Store Tests
- Free Calibration & Configuration Software
- Innovative Patented Technology
- ISO17025 Accredited Calibration Certificates
- Intrinsically Safe

Handheld Pressure Calibrators

Pressure Range	Pressure Accuracy	Vacuum Accuracy	Operating Temp. Range	IP Rating	Pressure Sensors	Pressure Connection	Datalogging	Differential Pressure	Absolute Pressure	Read Temperature	Read Electrical	24 VDC Power Supply	Switch Test	APM External Pressure Module	Intrinsically Safe	Model
Vacuum to 15 000 psi	± 0.035% Rdg	± 0.05% FS	-20 to 50° C	IP65	1 or 2	CPF Female		✓	✓	✓	✓	✓	✓			HPC40 Series
Vacuum to 15 000 psi	± 0.1% Rdg	± 0.25% FS	-10 to 50° C	IP67	1	CPF Female	✓		✓							XP2i
Vacuum to 15 000 psi	± 0.025% Rdg	± 0.06% FS	-20 to 50° C	IP67	1 or 2	CPF Female	✓	✓	✓	✓			✓			nVision
Vacuum to 10 000 psi	± 0.2% Rdg	± 0.25% FS	-10 to 50° C	IP65	1	CPF Female										m1
Vacuum to 5000 psi	± 0.05% Rdg + 0.005% FS	± 0.25% Rdg	0 to 50° C	—	1 or 2	1/8" NPT Female				✓						30 Series
Vacuum to 3000 psi	± 0.25% Rdg	± 0.5% FS	-10 to 50° C	IP65	1	CPF Female										m1M
Vacuum to 300 psi	± 0.02% Rdg + 0.015% FS	± 0.025% FS	-10 to 50° C	IP56	1	1/8" NPT Female			✓	✓	✓	✓	✓	✓		HPC600
Vacuum to 100 psi	± 0.1% Rdg	± 0.1% Rdg	-10 to 50° C	IP67	1	1/8" NPT Female	✓	✓								XP2i-DP
Pressure Range	Specifications (See the Data Sheets for complete specifications.)						Functions									Model

▶ From 18 to 28° C.
 ▶ Typical.
 ▶ Plus either 0.004 or 0.01 psi.
 ▶ 1/4" NPT M, 1/4" BSP M, or M20 M adapter included.
 ▶ 1/4" NPT M and 1/4" BSP M adapters included.

Deadweight Testers

Pressure Range	Standard Pressure Accuracy	Optional Pressure Accuracy (Rdg)	Maximum Pressure	Minimum Pressure	Minimum Increment	Pressure Connection*	Dual Piston Available	Dual Column Available	Tripod Compatibility	5m. Incremental Weight Sets	Hydraulic	Pneumatic	Self Contained	Self Regulating Ball Type	Included Carrying Case	Model*
10 psi to 15 000 psi	± 0.015% Rdg	± 0.025%, ± 0.1%	15 000 psi	10 psi	5 psi	1/4" and 1/2" NPT F	✓	✓		✓	✓		✓		✓	Type T Series
10 psi to 3000 psi	± 0.1% Rdg	± 0.05%	3000 psi	10 psi	0.1 psi	1/4" NPT F	✓		✓		✓		✓		✓	HL Series
10 psi to 1500 psi	± 0.025% Rdg	—	1500 psi	10 psi	1 psi	7/16-20 37° AN4 M						✓		✓		HK Series
4 inH ₂ O to 301 psi	± 0.05% Rdg	± 0.025%, ± 0.015%	301 psi	4 inH ₂ O	1 inH ₂ O	1/8" NPT F			✓	✓	✓			✓	✓	RK Series
4 inH ₂ O to 30 psi	± 0.05% Rdg	± 0.025%, ± 0.015%	30 psi	4 inH ₂ O	1 inH ₂ O	1/4" NPT F			✓	✓	✓			✓	✓	PKII Series
Pressure Range	Specifications (See the Data Sheets for complete specifications.)						Functions									Model*

▶ With installed adapter to 1/4 tube fitting.
 ▶ Not included with dual column or 0.015% accuracy. These units are supplied with bench top column mounting plate and tubing.

* CPF connections are available for all deadweight tester models.



Of Reading Accuracy

Our gauge accuracy is defined as “percent of reading”. For example, a gauge with 0.1 percent of reading accuracy that displays 100 psi would be accurate to ± 0.1 psi at that pressure. At 50 psi, the same gauge would have an accuracy of ± 0.05 psi (twice as accurate). This versatility is why one of our gauges can replace 3 to 5 standard “of scale” rated gauges.

Temperature Compensation

Our active temperature compensation corrects sensors for changes in temperature within our specified ranges (up to -20 to 50°C). Without temperature compensation, the additional errors can quickly overwhelm the basic specification at common working temperatures.

Floating Ball Testers

While in operation, our pneumatic tester’s ball and weights float freely, which is virtually frictionless, supported only by a thin film of air. This eliminates the necessity to rotate the weights during testing and allows the user to concentrate on the instrument calibration.

Self-Regulating Design

The instrument’s built-in flow regulator automatically adjusts the input air flow to maintain the ball and weights in a float position. The regulator also compensates for variations in pressure from the air supply. Simply add or remove weights to generate your target pressure.

Leak-free Seal up to 10 000 psi

Our patented CPF fitting design maintains a leak-free seal up to 10 000 psi, with only finger-tightening. Improve safety with a self-venting weep hole, which alerts you, by leaking gas or test fluid, before you fully disconnect from a pressurized system. Each of our products either includes CPF fittings as standard, or can be adapted to our CPF line.